



DEME

Dredging, Environmental
& Marine Engineering

Soil Investigation for the construction of an Offshore Wind Farm at the Thorntonbank - Belgium

Dr. Ir Patrick Mengé

DEME – Dredging International N.V.



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009





Patrick Mengé

CONTENTS

- 1. Description of the project**
- 2. Soil Investigation setup**
- 3. Geophysical testing**
- 4. Boreholes and CPT's**
- 5. Other techniques**
- 6. Laboratory testing**
- 7. Conclusion**



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance


Namur, le 10 février 2009





Patrick Mengé

DESCRIPTION OF THE PROJECT



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance


Namur, le 10 février 2009





Patrick Mengé

DESCRIPTION OF THE PROJECT



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009





Patrick Mengé

DESCRIPTION OF THE PROJECT

Connection to the land network: 38 km of cable


Verkenningsboringen

Namen, 10 februari 2009




Les forages de

Namur, le 10 février





DESCRIPTION OF THE PROJECT





Patrick Mengé

SITE INVESTIGATION SETUP

- Site investigation Phase I + cable route: 2004; Phase II: 2008
- Focus on Phase I
- Desk Study (Tertiary and Quarternary Geology of the Belgian Shelf)
- Geophysical
 - Multibeam bathymetry
 - Seismic reflection testing
 - Side Scan Sonar
 - Magnetic survey
- Geotechnical
 - CPTU (deep and undep), where necessary with predrilling
 - Boreholes with disturbed and undisturbed sampling
 - Boreholes with pressiometer testing
 - Laboratory investigation (static and dynamic soil properties)

CPT at each wind turbine locations; no BH at each wind turbine location.
Geophysical testing assists to define optimal locations for BH's



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009







Patrick Mengé

DESK STUDY

SCIENTIFIC SUPPORT PLAN FOR A SUSTAINABLE DEVELOPMENT POLICY



- ✓ 1 BH Belgian Geological Survey on the Thorntonbank
- ✓ Document “Tertiary and quaternary Geology of the Belgian Continental Shelf”
*Verkenningsboring
Wommen, 10 februari 2009*






Patrick Mengé

GEOPHYSICAL TESTING



Bathymetry

- Depth: -10m TAW tot -25m TAW
- Sandwaves 5m high, 150m tot 200m long
- Seabottom sinks to the NW
- Orientation of the sandwaves NW-SE





Patrick Mengé


GEOPHYSICAL TESTING




Seismic reflection testing

- First reflector: quartair – tertiair
- Second reflector: clay – sand
- Third reflector: Transition from Maldegem to Aalter formation
- Fourth reflector: not defined; “deepest main reflector”

SE - NW



SW - NE



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009






Patrick Mengé

GEOPHYSICAL TESTING



Seismic reflection testing: Top of the Tertiary






Patrick Mengé

GEOPHYSICAL TESTING

Seismic reflection testing: Thickness of the quaternary



Namen, 10 februari 2009


Namur, le 10 février 2009



Patrick Mengé

GEOPHYSICAL TESTING

Side Scan Sonar: Visualisation of morphology and obstacles



Namen, 10 februari 2009

Namur, le 10 février 2009






Patrick Mengé

BOREHOLES AND CPT'S

- Testing over water: 'Nearshore'; land based techniques from on a jack-up pontoon
- Use of extra protection casings and support casings to bridge the gap between Jack-up and seabottom (20 to 30 m)
- Displacing jackup and installation of casings: working on tide
- CPT at each wind turbine location before BH (define levels of sampling)
- In this case: CPT depth had to be reached; upon refusal destructive predrilling was realised
- Offshore working:
 - Always CPT-U
 - High water pressures, calculation of q_t is necessary, certainly in soft soils
 - Zeroing of the CPT cone: at platform level or at seabottom level?
- CPT Refusal: because of maximum q_c , f_s , u , inclination, total thrust, elastic rebound of the tubes, any other unsafe situation



BOREHOLES AND CPT'S





Patrick Mengé

BOREHOLES AND CPT'S





Patrick Mengé

BOREHOLES AND CPT'S



BOREHOLES AND CPT'S




**Harms
Brunnenba**
27478 CUXHAVEN-OXSTE
TEL. 04723/3377
www.harms-brunnenbau.de



Patrick Mengé

BOREHOLES AND CPT'S





Patrick Mengé

BOREHOLES AND CPT'S

- Bottom plate for outer casings
- Alternative for penetration (with the help of a bailor)
- Important when the top soil needs to be tested






Patrick Mengé

BOREHOLES AND

CPT-U jacking system

Verkenningsboringen



Namen, 10 februari 2009





Patrick Mengé

BOREHOLES AND CPT'S






Patrick Mengé

BOREHOLES AND CPT'S

- BH's over water mainly using wire line techniques:
 - Bailor in sand
 - Hammering sampling techniques in cohesive materials
 - Core Drilling techniques in cohesive materials
 - Use of drilling fluids! Accepted for high quality sampling? Attention to system and pressures, maintain difference in levels between drilling with flushing and sampling)
- Sampling
 - Bailor: fully representative PSD?
 - Hammering techniques (e.g. Nordmeyer)
 - Thick walled tubes with casing: class of sample??
 - Thin walled tubes: effect of hammering?
 - Core drilling techniques (e.g. GeoBor)
 - In which soil types succesfull operation?
 - Quality of samples depending on soil type.
 - Push-in techniques with flushing fluid pressure
 - Thin walled tubes
 - Piston samplers



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009





Patrick Mengé

BOREHOLES AND CPT'S

- BH advancement with bailor in sand
- Sampling: mixing over 1 m



Verkenningsboring

Namen, 10 februari 2009





Patrick Mengé

BOREHOLES AND

- Samples in containers
(small/large)





Patrick Mengé

BOREHOLES AND CPT

- Down the hole sampler BPE
- Thick walled samples in PVC liner
- With core catcher








Patrick Mengé

BOREHOLES AND CPT'S

- Down the hole sampler with heavier hammer (RKR system)
- Retrieval system
- Thick walled sample in PVC liner



Ramm-
Kern-
Rohr
System
RKR





*Verkenningsboringen
Namen, 10 februari 2009*





Patrick Mengé

BOREHOLES AND CPT'S

- PVC samples





Patrick Mengé

BOREHOLES AND CP

- Undisturbed thin walled samples





Patrick Mengé

BOREHOLES AND CPT'S

- Undisturbed samples: testing in the field





Patrick Mengé

BOREHOLES AND CPT'S

- Undisturbed thin walled samples



Verker
Namen, 10



BOREHOLES AND CPT'S

- If possible samples are withdrawn without drilling
- Very often drilling with flushing is necessary
- Other possibility: hollow stem auger is not (often) used over water





Figure 11.3 Hollow stem auger. (a) Plugged while advancing auger. (b) Plug removed and sampler inserted to sample soil below auger.





Patrick Mengé

BH log: according to BS 5930



BOREHOLES AND CPT'S

Marine Sampling Holland		Borehole Number I5 (Page 1 of 3)	
		Project number : 4142 GR Drilled by : Hams Brunnenbau Logged by : G.T. de Vries Drawn by : G.T. de Vries	
Client: GeoSea N.V. Haven 1025 - Scheldekaai 30 B2070 Zwijndrecht, Belgium		Date Started : 21-02-2008 Date Completed : 24-02-2008 Drilling Method : cable percussion / rotary flush	
Project name: Wind Farm Thornton Bank Phase 2 Contract name: Site Investigation 2008		Casing diameter 1 : 324 mm. till 15.6 m. depth Casing diameter 2 : 219 mm. till 29.5 m. depth	
Sampler Type: (K) Core sample in liner, BPE 150 - centered free fall tool (B) Disturbed sample from borer or from cutting shoe / core catcher after K sample (UP) Thin-walled tube sample / BPE 150 - centered free fall tool		Depth (m) Samples Depth from (m) Depth to (m) Blow Count Lab test program Pos.: I5	
Depth in Metres	elev. rel. to TAW -15.6	GRAPHIC	DESCRIPTION
0	-16		slightly silty SAND, well sorted, yellowish brown, fine to medium grained with some shell fragments (< 5 mm.).
1	-17		SAND, brownish grey, fine to medium grained with shell fragments (< 5 mm.).
2	-18		slightly gravelly SAND, brownish grey, fine to medium grained with shell fragments < 5 mm.
3	-19		very sandy GRAVEL to very gravelly SAND with some cobbles, brownish grey, sandfraction medium grained, gravel coarse, rounded (some angular to sub-angular), flint, slate and quartz, cobbles mainly flint, with many shells and shell fragments.
4	-20		slightly silty SAND, grey, medium grained, with shell fragments up to 5 mm.
5	-21		slightly gravelly SAND, grey, medium grained, with many shell fragments up to 1 cm.
6	-22		CLAY, light grey - brown, soft to firm
7	-23		
8	-24		
9	-25		
10	-26		

NOTE: No description of material in liners or thin walled tubes available. waiting for lab results

Laboratory tests:

(1) PSD, (2) mo s, (3) org. content, (4) calc. content, (5) plast. limits, (6) nat. water content, (7) volume mass, (8) oedometer, (9) CRS, (10) TX CD, (11) TX CU, (12) TX UU, (13) binder, (14) min/max density, (15) permeability

Borehole Number I5

(Page 1 of 3)

Marine Sampling Holland		Borehole Number I5 (Page 2 of 3)	
		Project number : 4142 GR Drilled by : Hams Brunnenbau Logged by : G.T. de Vries Drawn by : G.T. de Vries	
Client: GeoSea N.V. Haven 1025 - Scheldekaai 30 B2070 Zwijndrecht, Belgium		Date Started : 21-02-2008 Date Completed : 24-02-2008 Drilling Method : cable percussion / rotary flush	
Project name: Wind Farm Thornton Bank Phase 2 Contract name: Site Investigation 2008		Casing diameter 1 : 324 mm. till 15.6 m. depth Casing diameter 2 : 219 mm. till 29.5 m. depth	
Sampler Type: (K) Core sample in liner, BPE 150 - centered free fall tool (B) Disturbed sample from borer or from cutting shoe / core catcher after K sample (UP) Thin-walled tube sample / BPE 150 - centered free fall tool		Depth (m) Samples Depth from (m) Depth to (m) Blow Count Lab test program Pos.: I5	
Depth in Metres	elev. rel. to TAW -15.6	GRAPHIC	DESCRIPTION
10	-25		slightly gravelly SAND, grey, fine to medium grained, with shells (<2 cm) and shell fragments, gravel coarse to pebble size
11	-26		
12	-27		slightly gravelly SAND, grey, fine to medium grained, with weathered shell fragments and shells < 2 cm., few larger shells < 6 cm, gravel medium size, some clay- and organic clay pellets.
13	-28		
14	-29		slightly gravelly SAND, moderately sorted, grey, medium grained with many shell fragments and shells < 2 cm, few shells < 7 cm, gravel fine to medium, some wood, some clay pellets, one cobble-sized iron cemented sand pellet.
15	-30		
16	-31		shells and shell fragments
17	-32		slightly gravelly SAND, moderately sorted, with many shells and shell fragments < 2 cm, gravel rounded, fine to medium size
18	-33		sandy CLAY, stiff to very stiff
19	-34		
20	-35		CLAY, greenish grey, stiff to very stiff

NOTE: No description of material in liners or thin walled tubes available. waiting for lab results

Laboratory tests:

(1) PSD, (2) mo s, (3) org. content, (4) calc. content, (5) plast. limits, (6) nat. water content, (7) volume mass, (8) oedometer, (9) CRS, (10) TX CD, (11) TX CU, (12) TX UU, (13) binder, (14) min/max density, (15) permeability

Borehole Number I5


(Page 2 of 3)



BOREHOLES AND CPT'S

Geotechnical profile with BH's and CPT's – General Layering (Phase I)

- Loose sand
- Dense sand
- Gravel (transitionlayer)
- Stiff clay
- Dense sand (silty/clayey)
- Very dense silty/clayey sand with clay insertions
- Stiff clay





Patrick Mengé

OTHER TECHNIQUES: PRESSUREMETER

- Performed jointly by 2 companies: drilling company and other specialised company for PMT testing
- Conclusion: Results very poor



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009





Patrick Mengé

LABORATORY TESTING

- Classification testing (PSD, Plastic Limits, natural water content, carbonates content, organic content, bulk density)
- Compression testing
- Shear strength testing (vane, TX-UU, TX-CU, Simple Shear)
- Dynamic properties: Bender element testing combined with the above, cyclic TX and Simple Shear
- Analysis to material degradation under continuous cyclic loading
- Highest quality of samples needed!



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009






Patrick Mengé

CONCLUSIONS

- Succesful Offshore soil investigation needs good preparation (gathering of available info)
- Offshore Soil Investigation is combination of several techniques: geophysical, in situ testing and laboratory
- Offshore (nearshore) testing: use of land based techniques with special measures to bridge the gap between platform and seabottom
- Use of wire line techniques to speed up the drilling process
- Effect on disturbed and undisturbed sampling: do thick walled samples have to be rejected as high quality undisturbed samples?
- In the soil types encountered here good results with hammering techniques
- Quality of high level laboratory tests?



Verkenningsboringen

Namen, 10 februari 2009

Les forages de reconnaissance

Namur, le 10 février 2009



Thank you for your attention



DEME

Dredging, Environmental
& Marine Engineering

